

Metal Sales Product Catalog

Metal Roof & Wall Panels Products



Architectural
Commercial
Post Frame
Residential

ms metal salesTM
manufacturing corporation

THE METAL SALES DIFFERENCE

For more than 55 years, Metal Sales Manufacturing Corporation has earned a reputation as the premier provider of innovative metal building components and accessories. We've backed this reputation with the industry's largest professional sales and service team, supported by 21 branches located throughout the United States.

We offer a full line of exceptional quality metal roof and wall panels for agricultural, commercial, architectural, industrial and residential projects of every shape and size – new construction or retrofit.

But our technology and durable designs are only part of the story. Architects, contractors and installers appreciate the impeccable service from our highly trained professional staff, ready to answer any question, or help devise custom solutions to your building and energy saving needs.

- Serving the architectural, commercial, residential, industrial and agricultural markets for over half a century
- In-house engineering and design assistance available
- A wide selection of materials and finishes available, including MS Colorfast45®, ColorFit40™, PVDF, Weathering Steel, Aluminum, Stainless Steel and Copper
- Over 75 profiles available with matching trim and accessories
- All standard colors meet or exceed steep slope ENERGY STAR® requirements and many are also LEED compliant
- 21 convenient locations nationwide, including Alaska
- Quoting and shipping projects worldwide
- Up to 45 year Finish Warranties available
- Panel testing including FM-4471, UL 580, ASTM E 1592 and approvals including Miami-Dade County, ICC Evaluation Report and Florida Building Code (FBC) 2017
- 30 year Weather-Tight Warranty available (on select profiles) **WTW**
- Curving capabilities available – (see pages 3 and 8)

Metal Sales is dedicated to leading the metal building component industry, by setting new standards for operating efficiency, product design, active service management and lasting value. We strongly believe that by investing in our corporation, we will ensure the best products and services for our customers, high job satisfaction for our employees and continued innovation and growth for our industry.

Profile Selection

STANDING SEAM PANELS

Magna-Loc, Magna-Loc 180.....	3	WTW
Curved Magna-Loc.....	3	WTW
T-Armor Series™.....	4	WTW
Seam-Loc 24®.....	5	WTW
Snap-Loc 24.....	5	WTW
Vertical Seam, Vertical Seam Plus.....	6	WTW
Clip-Loc.....	6	WTW

CONCEALED FASTENED PANELS

Image II™.....	7	WTW
Mini-Batten, Curved Mini-Batten.....	8	
Box-Batten.....	8	
Maxi-Batten.....	8	
TL-17 Series.....	9	
Flush Face Series.....	10	
Concealed Fastened Wall Panels.....	11	WTW
Soffit Panel.....	12	

EXPOSED FASTENED PANELS

T10 Series.....	13
7/8" Corrugated.....	14
5V-Crimp.....	14
IC72-Panel.....	15
V-Line 32.....	15
Exposed Fastened Series.....	16, 17
Deep Rib Series.....	18
Industrial Rib Series.....	19

METAL BUILDING PANELS

PBR-Panel.....	20
R-Panel.....	20
PBU-Panel.....	20
U-Panel.....	20
Pro-Panel II®.....	21
Classic Rib®.....	21
1.25" Corrugated.....	22
2.5" Corrugated.....	22
Strongpanel.....	23
Span-Line 36A.....	23
DL-3 Panel.....	24
Bi-Rib.....	24
Delta Rib.....	24
Dual Rib.....	24

INSULATED WALL & ROOF PANELS

IMPower Series™.....	25
----------------------	----

SECONDARY FRAMING

Retro-Master® and Metal-Over-Metal.....	26
Perforation, Mitered Corners, Curving Options.....	26
Secondary Framing.....	27
Coating Systems.....	27

Magna-Loc, Magna-Loc 180

- ▶ Architectural/structural flat pan standing seam roof panel
- ▶ 16" or 18" panel coverage, 2" rib height
- ▶ Gauges: 24 ga. standard, 22 ga. optional
- ▶ Minimum roof slope: 1/2:12
- ▶ Factory-applied side lap sealant
- ▶ Mechanically seamed side lap
- ▶ Concealed clip designed for thermal movement
- ▶ Accommodates 1/2" to 6" blanket insulation
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities






Testing and Approvals




- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction #506, 506A and 506B
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 1592 Roof Uplift
- ▷ ASTM E 1646 Water Penetration - none at 12 psf*
- ▷ ASTM E 1680 Air Leakage - 0.016 cfm/ft² at 12 psf*
- ▷ ASTM E 2140 Water Penetration, Static Head - none*
- ▷ Texas Department of Insurance Evaluation Report, RC-197
- ▷ Factory Mutual Approved, 1-90, 1-105, 1-165
- ▷ Miami-Dade County Approved, NOA 18-0901.01 and 18-0901.02
- ▷ ICC Evaluation Report, ESR-2385
- ▷ 2017 FBC Approved
 - Magna-Loc 24 ga. over 16 ga. Purlins, 10999.5
 - Magna-Loc 24 ga. over 5/8" Plywood, 11560.6
 - Magna-Loc 24 ga. over 22 ga. Metal Deck, 11560.7
 - Magna-Loc 0.032" or 0.040" Aluminum over 22 ga. Metal Deck, 10999.2
 - Magna-Loc 180 24 ga. over 16 ga. Purlins, 10999.6

*with tube sealant at clip locations




Striated



Pencil Ribs



Flat




Curved Magna-Loc 180

- ▶ Architectural/structural standing seam roof panel
- ▶ 16" panel coverage, 2" rib height
- ▶ 24 ga. standard
- ▶ Minimum radius 20'-0"
- ▶ Field and factory curving available
- ▶ Pre-applied side lap sealant
- ▶ Mechanically seamed side lap
- ▶ Concealed clip designed for thermal movement
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction #576, 577 and 583
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 1592 Roof Uplift
- ▷ ASTM E 1646 Water Penetration
- ▷ ASTM E 1680 Air Leakage
- ▷ 2017 FBC Approved
 - Magna-Loc 180 24 ga. over 16 ga. Purlins, 10999.6


Striated





T-Armor Series™

- ▶ Structural "T" standing seam roof panel
- ▶ 12", 16" and 18" panel coverage
- ▶ Rib Height: 2-3/8" and 3"
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Gauges: 24 ga. standard, 22 ga. and 20 ga. optional
- ▶ Aluminum: 0.032" and 0.040"
- ▶ Minimum roof slope: 1/2:12
- ▶ Integral mechanically seamed side lap
- ▶ "T" style rib allows for easy single panel replacement
- ▶ Factory-applied side lap sealant
- ▶ Concealed clip designed for thermal movement
- ▶ Accommodates 1/2" to 6" blanket insulation
- ▶ Applies over open framing or solid substrate
- ▶ Contact Metal Sales for load-carrying capabilities


Panel Cap Before Seaming




Panel Cap After Seaming




Flat




Striated




Pencil Rib




Minor Rib



Plank



Mesa




Testing and Approvals

- ▶ UL 263, Fire Resistance Rating — per assembly
- ▶ UL 580, Class 90 Uplift, Construction #268, 268A and 268B
- ▶ UL 790, Class A Fire Resistance Rating — per assembly
- ▶ UL 1897, Uplift Load
- ▶ UL 2218, Class 4 Impact Resistance
- ▶ ASTM E 283 Air Infiltration
- ▶ ASTM E 330 Uniform Static Air Pressure Difference
- ▶ ASTM E 331 Water Penetration
- ▶ ASTM E 1592 Roof Uplift
- ▶ ASTM E 1646 Water Penetration
- ▶ ASTM E 1680 Air Leakage
- ▶ ASTM E 1886, 1996 Impact
- ▶ ASTM E 2140 Water Penetration, Static Head - none*
- ▶ TAS 201, 203 Impact
- ▶ TAS 100, Wind Driven Rain
- ▶ ICC 500 / FEMA 361
- ▶ ICC Evaluation Report, ESR-3743
- ▶ AAMA 501.1, Dynamic Water
- ▶ FM 4470, Foot Traffic

*with tube sealant at clip locations

Seam-Loc 24®

- ▶ Structural trapezoidal standing seam roof panel
- ▶ 24" or 18" panel coverage, 2-11/16" rib height
- ▶ Gauges: 24 ga. standard, 22 ga. optional
- ▶ Minimum roof slope: 1/4:12
- ▶ Factory-applied side lap sealant
- ▶ Pittsburgh double flat locking mechanically seamed side lap
- ▶ Concealed clip designed for thermal movement
- ▶ Accommodates 1/2" to 6" blanket insulation
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities




Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #197 and 197A
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 1592 Roof Uplift
- ▷ ASTM E 1646 Water Penetration
- ▷ ASTM E 1680 Air Leakage
- ▷ Factory Mutual Approved, 1-90 and 1-165
- ▷ 2017 FBC Approved
 - 24" wide over 16 ga. Purlins, 10999.8
 - 24" wide (with clamps) over 16 ga. Purlins, 10999.9



Snap-Loc 24®

- ▶ Structural trapezoidal standing seam roof panel
- ▶ 24" panel coverage, 3" rib height
- ▶ Gauges: 24 ga. standard, 22 ga. optional
- ▶ Minimum roof slope: 1/4:12
- ▶ Factory-applied side lap sealant
- ▶ Snap-together panel system
- ▶ Concealed clip designed for thermal movement
- ▶ Accommodates 1/2" to 6" blanket insulation
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Uplift, Construction, #240
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 330, Uniform Static Air Pressure Difference
- ▷ ASTM E 1592 Roof Uplift
- ▷ ASTM E 1646 Water Penetration
- ▷ ASTM E 1680 Air Leakage




Vertical Seam


- ▶ Architectural/structural standing seam panel
- ▶ Panel Coverage: 12", 16" or 18"
- ▶ Rib Height: 1-3/4"
- ▶ Gauges: 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ Snap-together panel system with factory-applied side lap sealant
- ▶ Minimum roof slope over open framing 3:12
- ▶ Minimum roof slope over solid substrate 1:12
- ▶ Concealed clip designed for unlimited thermal movement
- ▶ Accommodates up to 4" blanket insulation
- ▶ Finishes: PVDF, MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Vertical Seam Plus


- ▶ Square Batten Cap option for Vertical Seam Panel
- ▶ Available at the Fontana Branch only



Striated



Flat Pan



Testing and Approvals

- ▶ UL 263, Fire Resistance Rating — per assembly
- ▶ UL 580, Class 90 Wind Uplift, Construction, #254, 255, 261, 303, 342, 343, 436, 445, 446, 447, 448, 508 and 508A
- ▶ UL 790, Class A Fire Resistance Rating — per assembly
- ▶ UL 2218, Class 4 Impact Resistance
- ▶ ASTM E 1592 Roof Uplift
- ▶ ASTM E 1646 Water Penetration
- ▶ ASTM E 1680 Air Leakage
- ▶ Miami-Dade County Approved, NOA 18-1227.01
- ▶ Texas Department of Insurance Evaluation Report, RC-412
- ▶ ICC Evaluation Report, ESR-2385
- ▶ 2017 FBC Approved
 - 26 ga. over 1/2" Plywood, 11560.12 (16" Panel)
 - 24 ga. over 1/2" Plywood, 11560.10 (16" Panel)
 - 24 ga. over 1/2" Plywood, 11560.13 (16" Panel)
 - 24 ga. over 1/2" Plywood, 11560.11 (18" Panel)
 - 24 ga. over 1/2" Plywood, 11560.14 (18" Panel)
 - 0.032" Aluminum over 7/16" OSB, 14645.6 (16" Panel)
 - 0.032" Aluminum over 5/8" Plywood, 14645.7 (16" Panel)



Clip-Loc

- ▶ Architectural/structural integral standing rib roof system
- ▶ Snap-together panel system
- ▶ 16" panel coverage, major rib: 8" centers, 1-5/8" rib height
- ▶ Gauges: 26 ga., 24 ga. standard and 22 ga. optional
- ▶ Minimum roof slope: 1:12
- ▶ Applies over open framing or solid substrate
- ▶ Concealed clip designed for thermal movement
- ▶ Accommodates up to 4" blanket insulation
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals

- ▶ UL 263, Fire Resistance Rating — per assembly
- ▶ UL 580, Class 90 Wind Uplift, Construction, #586 and 586A
- ▶ UL 790, Class A Fire Resistance Rating — per assembly
- ▶ UL 1897, Uplift Tests for Roof Covering Systems
- ▶ UL 2218, Class 4 Impact Resistance
- ▶ ASTM E 1592 Roof Uplift
- ▶ ASTM E 1680 Air Leakage
- ▶ ICC Evaluation Report, ESR-2385




Image II

- ▶ Architectural concealed direct-fastened roof panel
- ▶ Panel coverage: 12" or 16"
- ▶ 1" rib height
- ▶ Gauges: 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over solid substrate with 30# felt underlayment
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities




Striated

Fastening legs vary by branch

Slotted Flat



Fastening Groove




16" Minor Rib

Fastening legs vary by branch

Slotted Flat



Fastening Groove





12" Minor Rib

Fastening legs vary by branch

Slotted Flat



Fastening Groove



Testing and Approvals

- ▶ UL 263, Fire Resistance Rating – per assembly
- ▶ UL 580, Class 90 Wind Uplift, Construction, #529
- ▶ UL 790, Class A Fire Resistance Rating – per assembly
- ▶ UL 2218, Class 4 Impact Resistance
- ▶ Miami-Dade County approved, NOA 18-0830.03
- ▶ Texas Department of Insurance Evaluation Reports, RC-162, RC-398 and RC-399
- ▶ ICC Evaluation Report, ESR-2385
- ▶ 2017 FBC Approved
 - 26 ga. over 5/8" Plywood, 11560.5
 - 26 ga. over 1/2" Plywood, 11560.4
 - 26 ga. over 7/16" OSB, 14645.12
 - 0.032" Aluminum over 7/16" OSB, 11560.2
 - 0.032" Aluminum over 5/8" Plywood, 11560.3



Mini-Batten


- ▶ Architectural standing seam roof panel
- ▶ 12", 16" or 18" panel coverage, minimum roof slope: 3:12
- ▶ Mini-Batten offers, 1" & 1-1/2" high rib utilizing a narrow batten cap
- ▶ Gauges: 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ Concealed clip designed for thermal movement
- ▶ Applies over solid substrate with 30# felt underlayment
- ▶ Finishes: PVDF, MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals


- ▶ UL 263, Fire Resistance Rating – per assembly
- ▶ UL 580, Class 90 Wind Uplift, Construction, #397, 397A and 430 (1" Mini-Batten)
- ▶ UL 580, Class 90 Wind Uplift, Construction, #352 (1-1/2" Mini-Batten)
- ▶ UL 790, Class A Fire Resistance Rating – per assembly
- ▶ UL 2218, Class 4 Impact Resistance
- ▶ ASTM E 283 Air Leakage
- ▶ ASTM E 331 Water Penetration

Curved Mini-Batten


- ▶ Minimum radius 4'-0"



1" Mini-Batten



1.5" Mini-Batten



Box-Batten/Maxi-Batten

- ▶ Architectural standing seam roof panel
- ▶ 12", 16", or 18" panel coverage, minimum roof slope: 3:12
- ▶ Maxi-Batten offers, 1-5/8" x 1-7/8"
- ▶ Box-Batten offers 1-1/2" x 1-1/2" cap
- ▶ Gauges: 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ Concealed clip designed for thermal movement
- ▶ Applies over solid substrate with 30# felt underlayment
- ▶ Finishes: PVDF, MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities




Testing and Approvals

- ▶ UL 263, Fire Resistance Rating – per assembly
- ▶ UL 580, Class 90 Wind Uplift, Construction, #398 and 398A (Maxi-Batten)
- ▶ UL 790, Class A Fire Resistance Rating – per assembly
- ▶ UL 2218, Class 4 Impact Resistance
- ▶ ASTM E 283 Air Leakage
- ▶ ASTM E 331 Water Penetration


Box-Batten

Available from Sellersburg, IN branch



Maxi-Batten

Available from Fontana, CA branch



TL-17 Series

- ▶ Concealed direct-fastened panel for wall, soffit, fascia or liner applications
- ▶ 12" panel coverage
- ▶ 1-1/2" panel depth
- ▶ 30'-0" maximum length, press-broke panel
- ▶ Gauges: 24 ga. standard, 22 ga., 20 ga. and 18 ga. optional
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Optional material: stainless steel, aluminum and copper
- ▶ Custom capabilities include:
 - Perforated panels for wind screens and liner panels
- ▶ Optional Finishes: Multi-pass Kynar 500®, Marblique®, Plastisol and Polyester
- ▶ Contact Metal Sales for load-carrying capabilities


TL-17 & TL-17D Wall




Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ ASTM E 283 Air Leakage
- ▷ ASTM E 330 Uniform Static Air Pressure Difference
- ▷ ASTM E 331 Water Penetration
- ▷ ASTM E 1592 Roof Uplift


TL-17




TL-17A




TL-17C



TL-17D



TL-1222



Flush Face Series

- ▶ Concealed direct-fastened panel for wall, soffit, fascia or liner applications
- ▶ 12" panel coverage
- ▶ 1-1/2" panel depth
- ▶ 45'-0" maximum length, roll-formed panel
- ▶ Gauges: 24 ga. standard, 22 ga. and 20 ga. optional
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Optional material: stainless steel, aluminum and copper
- ▶ Custom capabilities include:
 - Perforated panels for wind screens and liner panels
- ▶ Optional Finishes: Multi-pass Kynar 500®, Marblique, Plastisol and Polyester
- ▶ Contact Metal Sales for load-carrying capabilities




TLC-1 Wall


Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ ASTM E 283 Air Infiltration
- ▷ ASTM E 330 Uniform Static Air Pressure Difference
- ▷ ASTM E 331 Water Penetration
- ▷ ASTM E 1592 Roof Uplift


TLC-1




TLC-2




TLC-3




TLC-4



TLC-9



TLC-10



Concealed Fastened Wall Panels

- ▶ Concealed direct-fastened panel for wall applications
- ▶ Panel lengths available from 5'-0" to 30'-0" max*
- ▶ Gauges: 24 ga. standard; 22 ga. optional
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Horizontal and Vertical installation
- ▶ Common joinery allows panel profile to be mixed and matched for increased design flexibility
- ▶ High-strength clip allows for thermal and seismic movement

*Standard max length of 20' for AP1-1212, CN88-1212 and EM1-1212.


Testing and Approvals

- ▶ ASTM E 283 Air Infiltration
- ▶ ASTM E 330 Load Testing
- ▶ ASTM E 331 Water Penetration
- ▶ ASTM E 1592 Roof Uplift


Apex Series™

Symmetrical Rib

AP1-1212




AP1-1653




Contempra Series™

Asymmetrical Rib

CN88-1212




CN88-1653




Empire Series™

Box Rib


EM1-1212




EM1-1653




EM15-126




EM15-168




EM15-1266




EM15-1275



EM15-1284



EM15-1293



Soffit Panel

- ▶ Concealed direct-fastened system for soffit, wall, fascia or liner applications
- ▶ 12" panel coverage
- ▶ 1" depth
- ▶ Max Panel Length: 26 ga. 5'-0", 24 ga. 20'-0" and 0.032" Alum 25'-0"
- ▶ Gauges: 26 ga., 24 ga. and 0.032" aluminum
- ▶ Lanced and Perforated versions are available
- ▶ Applies over solid substrate with 30# felt underlayment
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities


Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ ASTM E 283 Air Infiltration
- ▷ ASTM E 330 Uniform Static Air Pressure Difference
- ▷ ASTM E 331 Water Penetration
- ▷ 2017 FBC Approved
- 24 ga. panel over 16 ga. Purlins, 9482.5




Lanced Soffit V-Grooves


Perforated V-Grooves




Flat




V-Grooves




Lanced Flat



Lanced V-Grooves



Perforated Flat



T10 Series

- ▶ Exposed direct-fastened panel for wall, soffit, fascia and liner panel
- ▶ Applies over open framing or solid substrate
- ▶ 28", 30" and 36" panel coverages, 1-1/2" rib height
- ▶ 90° vertical box ribs on 4", 6", 9" and 12" centers
- ▶ Optional material: stainless steel, aluminum and copper
- ▶ Gauges: 24 ga. standard, 22 ga., 20 ga. and 18 ga. optional
- ▶ Custom capabilities include:
 - Perforated panels for wind screens and liner panels
- ▶ Standard Finish: PVDF and Acrylic Coated Galvalume®
- ▶ Optional Finishes: Multi-pass Kynar 500®, Marblique, Plastisol and Polyester
- ▶ Contact Metal Sales for load-carrying capabilities


Other profiles are available. Please inquire.




Testing and Approvals

- ▷ UL 263, Fire Resistance Rating — per assembly
- ▷ UL 2218, Class 4 Impact Rating


T10-A Wall Panel




T10-B Wall Panel



T10-C Wall Panel



T10-D Wall Panel




7/8" Corrugated

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 32" roof coverage (34-2/3" wall coverage)
- ▶ 7/8" rib height, 2-2/3" centers
- ▶ Gauges: 26 ga. and 24 ga. standard, 22 ga. and 20 ga. optional
- ▶ Optional materials: stainless steel, aluminum, copper and weathering steel
- ▶ Minimum roof slope: 1:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities


Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 283 Air Infiltration
- ▷ ASTM E 330 Uniform Static Air Pressure Difference
- ▷ ASTM E 331 Water Penetration
- ▷ ASTM E 1592 Roof Uplift Capacity
- ▷ ASTM E 1646 Water Penetration
- ▷ ASTM E 1680 Air Leakage
- ▷ Texas Department of Insurance Evaluation Report, RC-409
- ▷ ICC Evaluation Report, ESR-2385
- ▷ 2017 FBC Approved
 - 24 ga. roof panel over 16 ga. Purlins, 10999.1
 - 24 ga. wall panel over 16 ga. Girts, 9482.1

Roof Panel



Wall Panel




5V-Crimp

- ▶ Exposed direct-fastened roof panel, traditional "V" rib
- ▶ 24" panel coverage
- ▶ 1/2" rib height
- ▶ Gauges: 29 ga. and 26 ga. standard, 0.032" Aluminum optional
- ▶ Minimum roof slope: 3:12
- ▶ Applies over solid substrate with 30# felt underlayment
- ▶ Finishes: MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #453 and 579
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Rating
- ▷ Miami-Dade County Approved, NOA 18-0313.02 (26 gauge)
- ▷ Miami-Dade County Approved, NOA 14-1227.02 (0.032" Aluminum)
- ▷ Texas Department of Insurance Evaluation Report, RC-160
- ▷ 2017 FBC Approved
 - 26 ga. over 5/8" Plywood, 14645.2 and 14645.3
 - 26 ga. over 7/16" OSB, 14645.4
 - 0.032" Aluminum over 7/16" OSB, 11560.1




IC72-Panel


- ▶ Exposed direct-fastened industrial panel
- ▶ Roof and wall applications
- ▶ 36" panel coverage, minimum roof slope: 1:12
- ▶ 1-1/2" rib height at 7.2" centers
- ▶ Gauges: 24 ga. standard, 22 ga. and 20 ga. optional
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Roof Panel



Wall Panel



Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ ASTM E 283 Air Infiltration
- ▷ ASTM E 330 Uniform Static Air Pressure Difference
- ▷ ASTM E 331 Water Penetration
- ▷ ICC Evaluation Report, ESR-2385




V-Line 32

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 32" panel coverage
- ▶ Trapezoidal rib on 4-9/16" centers
- ▶ 1-3/8" rib height
- ▶ Gauges: 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ Minimum roof slope: 1:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #187
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance



Exposed Fastened Series

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ Applies over open framing or solid substrate
- ▶ Panel coverage: 32" to 44"
- ▶ Rib height: 5/8" to 1-3/4"
- ▶ Optional material: stainless steel, aluminum and copper
- ▶ Gauges: 24 ga. standard, 22 ga., 20 ga. and 18 ga. optional
- ▶ Minimum roof slope: 1:12
- ▶ Standard Finish: PVDF and Acrylic Coated Galvalume®
- ▶ Optional Finishes: Multi-pass Kynar 500®, Marblique, Plastisol and Polyester
- ▶ Contact Metal Sales for load-carrying capabilities

Other profiles are available. Please inquire.





T2630 Panel





T1 Roof

T1 Wall





T2 Roof

T2 Wall





T3 Roof

T3 Wall





T4 Roof

T4 Wall



T5 Roof



T5 Wall







T6-A Roof

T6-A Wall





T7 Roof

T7 Wall





T7-A Roof

T7-A Wall



T11-A Roof



T11-A Wall



T12 Roof/Wall



T16-L Wall

Same profile for Roof and Wall



T16-E Roof


T16-E Wall



Deep Rib Series



- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ Applies over open framing or solid substrate
- ▶ Various panel coverages
- ▶ 2", 4" and 4-1/2" rib heights
- ▶ Trapezoidal ribs on various centers
- ▶ Optional material: stainless steel, aluminum and copper
- ▶ Gauges: 24 ga. standard, 22 ga., 20 ga. and 18 ga. optional
- ▶ Minimum roof slope: 1:12
- ▶ Custom capabilities include:
 - Perforated panels for wind screens and liner panels
- ▶ Standard Finish: PVDF and Acrylic Coated Galvalume®
- ▶ Optional Finishes: Multi-pass Kynar 500®, Marblique, Plastisol and Polyester
- ▶ Contact Metal Sales for load-carrying capabilities

Other profiles are available. Please inquire.





T2630 Roof

T2630 Wall





T2832 Roof

T2832 Wall





T15 Roof

T15 Wall





T25 Roof

T25 Wall



TDR-6 Roof

TDR-6 Wall



Industrial Rib Series

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ Applies over open framing or solid substrate
- ▶ 24" and 30" panel coverages
- ▶ 3" and 3-1/2" rib heights
- ▶ Trapezoidal ribs on various centers
- ▶ Optional material: stainless steel, aluminum and copper
- ▶ Gauges: 24 ga. standard, 22 ga., 20 ga. and 18 ga. optional
- ▶ Minimum roof slope: 1:12
- ▶ Custom capabilities include:
 - Perforated panels for wind screens and liner panels
- ▶ Standard Finish: PVDF and Acrylic Coated Galvalume®



Other profiles are available. Please inquire.



T13-B Wall



T13 Roof

T13 Wall





T13-A Roof

T13-A Wall





T13-B Roof

T13-B Wall





T14 Roof

T14 Wall



PBR-Panel, R-Panel

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 36" panel coverage
- ▶ Trapezoidal rib on 12" centers
- ▶ 1-1/4" rib height
- ▶ PBR-Panel Gauges: 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ R-Panel Gauges: 26 ga. standard
- ▶ Minimum roof slope: 1:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities





Testing and Approvals

- ▷ UL 580, Class 90 Wind Uplift, Construction, #161
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 455 Diaphragm Test
- ▷ Miami-Dade County Approved, NOA 18-0131.05 and 18-0131.04 (24 ga. roof & wall)
- ▷ Texas Department of Insurance Evaluation Reports, RC-198, RC-265, RC-279, RC-391
- ▷ ICC Evaluation Report, ESR-2385 (R-Panel)
- ▷ 2017 FBC Approved
 - 26 ga. over 16 ga. Purlins, 10999.7
 - 26 ga. over 16 ga. Girts, 9482.4
 - 26 ga. over 1/2" Plywood, 14645.12



PBU-Panel, U-Panel

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 36" panel coverage
- ▶ Trapezoidal rib on 6" centers
- ▶ 3/4" rib height
- ▶ Gauges: 29 ga., 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ Minimum roof slope: 1:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #39
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ Texas Department of Insurance Evaluation Report, RC-196
- ▷ ICC Evaluation Report, ESR-2385

Pro-Panel II®

- ▶ Exposed direct-fastened, low profile panel for roof and wall
- ▶ 36" panel coverage
- ▶ Trapezoidal rib on 9" centers
- ▶ 5/8" rib height
- ▶ Gauges: 29 ga. and 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 455 Diaphragm Test
- ▷ 2017 FBC Approved
 - 29 ga. over 1/2" Plywood, 14645.14



Pro-Panel II



Overlap Leg



Pro-Panel II

Available in select branches only

Alternate Overlap Leg




Classic Rib®

- ▶ Exposed direct-fastened, low profile panel for roof and wall
- ▶ 36" panel coverage
- ▶ Trapezoidal rib on 9" centers
- ▶ 3/4" bell-top rib height
- ▶ Gauges: 29 ga. and 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals


- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #560 and 584
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 455 Diaphragm Test
- ▷ ASTM E 564-95 Diaphragm Test
- ▷ Miami-Dade County Approved, NOA 16-0218.02
- ▷ Texas Department of Insurance Evaluation Reports, RC-161 and RC-391
- ▷ ICC Evaluation Report, ESR-2385
- ▷ 2017 FBC Approved

–29 ga. over 2x Purlins, 10999.4	–26 ga. over 5/8" Plywood, 14645.9
–29 ga. over 2x Girts, 9482.3	–26 ga. over 16 ga. Girts, 9482.2
–29 ga. over 7/16" OSB, 14645.10	–26 ga. over 16 ga. Purlins, 10999.3
–29 ga. over 1/2" Plywood, 14145.13	–0.032" Aluminum over 7/16" OSB, 14645.5
–29 ga. over 1/2" Plywood, 14645.8	



1.25" Corrugated

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 24" panel coverage
- ▶ Corrugated ribs on 1-1/4" centers
- ▶ 1/4" rib height
- ▶ Gauges: 29 ga. and 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Testing and Approvals


- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #161
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance




Roof

2.5" Corrugated

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 24" panel coverage (wall)
- ▶ 21-1/3" panel coverage (roof)
- ▶ Corrugated ribs on 2-2/3" centers
- ▶ 1/2" rib height
- ▶ Gauges: 29 ga. and 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Wall




Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ Texas Department of Insurance Evaluation Report, RC-159
- ▷ ICC Evaluation Report, ESR-2385
- ▷ 2017 FBC Approved
–26 ga. over 5/8" Plywood, 14645.1



Strongpanel

- ▶ Exposed direct-fastened roof and wall panel
- ▶ 36" panel coverage
- ▶ 5/8" rib height
- ▶ Classic board and batten design, on 9" centers
- ▶ Gauges: 29 ga. and 28 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Strongcoat45® and Galvanized
- ▶ Contact Metal Sales for load-carrying capabilities




Testing and Approvals

- ▷ UL 263, Fire Resistance – per assembly
- ▷ UL 580, Class 90 Wind Uplift, Construction, #161
- ▷ UL 790, Class A Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ Texas Department of Insurance, RC-405 and RC-406



Span-Line 36A

- ▶ Exposed direct-fastened wall panel
- ▶ 36" panel coverage
- ▶ 1-1/8" rib height
- ▶ Inverted trapezoidal ribs on 12" centers
- ▶ Gauges: 26 ga. and 24 ga. standard, 22 ga. optional
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45®, PVDF and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities



Testing and Approvals

- ▷ UL 263, Fire Resistance Rating – per assembly
- ▷ UL 2218, Class 4 Impact Resistance
- ▷ ASTM E 330 Uniform Static Air Pressure Difference
- ▷ 2017 FBC Approved
–26 ga. over 16 ga. Girts, 9482.6




DL-3 Panel

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 36" panel coverage
- ▶ 1/2" rib height
- ▶ Trapezoidal ribs on 3" centers
- ▶ Gauges: 29 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45® and Bare Galvanized
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals

- ▶ ASTM E 1592 Structural Performance




Bi-Rib

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 36" panel coverage
- ▶ 7/16" rib height
- ▶ Double trapezoidal ribs on 9" centers
- ▶ Gauges: 29 ga. and 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities

Testing and Approvals

- ▶ UL 263, Fire Resistance – per assembly
- ▶ UL 790, Class A Fire Resistance Rating – per assembly
- ▶ UL 2218, Class 4 Impact Resistance




Delta Rib

- ▶ Exposed direct-fastened panel for roof and wall applications
- ▶ 24" panel coverage
- ▶ 13/16" rib height
- ▶ Trapezoidal rib on 8" centers
- ▶ Gauges: 29 ga. and 26 ga. standard
- ▶ Minimum roof slope: 3:12
- ▶ Applies over open framing or solid substrate
- ▶ Finishes: MS Colorfast45® and Acrylic Coated Galvalume®
- ▶ Contact Metal Sales for load-carrying capabilities


Testing and Approvals

- ▶ UL 263, Fire Resistance Rating – per assembly
- ▶ UL 790, Class A Fire Resistance Rating – per assembly
- ▶ UL 2218, Class 4 Impact Resistance



Dual Rib

- ▶ Mill-finished diamond-embossed aluminum
- ▶ Exposed direct-fastened, low profile panel for roof and wall
- ▶ 36" panel coverage
- ▶ 3/4" bell-top rib height
- ▶ Twin trapezoidal ribs on 9" centers
- ▶ Thickness: 0.0155" and 0.018"
- ▶ Minimum roof slope: 3:12
- ▶ Contact Metal Sales for load-carrying capabilities




IMPower Series™

- ▶ Insulated metal wall and roof systems
- ▶ Factory-injected foam insulation between dual steel facings
- ▶ Closed cell insulating core provides approximately R-8 per inch
- ▶ Panel Coverage: 40"
- ▶ Wall Panel Thickness: 2", 2.5", 3" and 4"
- ▶ Roof Panel Thickness: 2.5", 3.25", 4", 5" and 6"
- ▶ Gauges: 26 ga. standard 24 ga. and 22 ga. optional
- ▶ Finishes: PVDF and SMP coatings
- ▶ Contact Metal Sales for load-carrying capabilities


Testing and Approvals

- ▷ ASTM E 283 Air Infiltration
- ▷ ASTM E 331 Water Penetration
- ▷ ASTM E 1646 Water Penetration
- ▷ ASTM E 1680 Air Leakage


DM40 Double Mesa Wall




FL40 Flat Wall




SR2 Standing Seam Roof




HE40 Heavy Embossed Wall




HE40A AdobeTexture™ Wall



HR3 High Rib Roof



ST40 Striated Wall



Retro-Master® System

Solutions for existing flat roofs

Retro-Master® is a complete retrofit roof system that easily and affordably transforms old and failing roofs into a new code-compliant and energy-efficient sloped metal roof.


As a single-source solution Retro-Master® retrofit roof system is backed by a 20 year weathertight warranty and an industry-leading 45 year paint finish warranty. It is the ideal solution for schools, universities, retail centers, industrial or office building, military or any other building needing a new, long-lasting, high performance roof.

Solutions for existing sloped metal roofs

If your building has an existing metal roof in need of replacement, Retro-Master® is the most complete and convenient solution. This easy, efficient and virtually waste-free system is installed over your existing roof, allowing your business to operate uninterrupted.


Metal-Over-Metal Reroof Solution combines high quality Metal Sales roof panels with a patented Roof Hugger® sub-purlin retrofit framing system to deliver a new, structurally sound roof that will stand the test of time.

Post-Purlin Retrofit System



New metal roof panels over existing flat roof.

Metal over Metal System



New metal roof panels over existing sloped metal panels.

Perforation

- Perforated panels are an aesthetic design solution
- Wide array of panel profiles
- Available gauges: 24, 22, 20 or 18
- Windscreens, balcony railings, equipment and concealment screens, ventilation and interior liner



Mitered Corners

- Non-Insulated panels up to 3" deep
- Vertical & Horizontal applications
- Profile widths or modules up to 36"
- +/- 90 Degrees (Inside – Outside – Double Corners)
Corner leg dimensions up to 4'-0" in either direction



Curved Panel Options

- Factory and site curving options
- Available profiles: Magna-Loc 180 and Mini-Batten
- Magna-Loc 180: 20' min radius, no max radius
- Mini-Batten: min Convex radius: 4'
min Concave radius: 6'




Secondary Framing


- ▶ Ceers and Zees 4" to 12" deep with 2-1/2" to 4" flange widths
- ▶ Symmetrical and unsymmetrical flanges
- ▶ Red Oxide finish ASTM A 1011 Grade 50, Class 2 (55 ksi min yield)
- ▶ Galvanized finish ASTM A 653 Grade 50, Class 2 (55 ksi min yield)
- ▶ Single Slope Eave Struts for high side applications
- ▶ Double Slope Eave Struts for low side applications
- ▶ LGSI Purlins available



CEES, ZEES AND EAVE STRUTS



CHANNELS, HAT SECTIONS AND ANGLES



Other Components are available. Please inquire.

Coating Systems

Meet or exceed codes and standards


Our advanced coating technology ensures Metal Sales finishes and colors meet demonstrated energy performance requirements established by ENERGY STAR® and the Cool Roof Rating Council (CRRC) for solar reflectance and thermal emittance for steep sloped and/or low sloped buildings.

Benefits of cool colors


Cool roof colors are offered from an engaging palette of light neutrals to dark saturated hues that respect the environment and help achieve your vision. Cool roofs may also contribute to other strategies for optimizing energy performance. Energy savings and other direct benefits are contingent upon building type, location and use.

Substrate Materials

Our line of durable substrate materials includes steel, stainless steel, weathering steel, copper and aluminum. Your Metal Sales representative has technical information on material and coating compatibility.



Metal Sales Branch Locations



ANCHORAGE, ALASKA

4625 Old Seward Highway
Anchorage, AK 99503
866.640.7663 • 907.646.7664/Fax

BAY CITY, MICHIGAN

5209 Mackinaw Road
Bay City, MI 48706
888.777.7640 • 888.777.0112/Fax

DEER LAKE, PENNSYLVANIA

29 Pinedale Industrial Road
Orwigsburg, PA 17961
800.544.2577 • 800.544.2574/Fax

DENVER, COLORADO

7990 East I-25, Frontage Road
Longmont, CO 80504
800.289.7663 • 800.289.1617/Fax

DETROIT LAKES, MINNESOTA

1435 Egret Avenue
Detroit Lakes, MN 56501
888.594.1394 • 888.594.1454/Fax

FONTANA, CALIFORNIA

14213 Whittram Avenue
Fontana, CA 92335
800.782.7953 • 909.829.9083/Fax

FORT SMITH, ARKANSAS

7510 Ball Road
Fort Smith, AR 72908
877.452.3915 • 479.646.5204/Fax

INDEPENDENCE, MISSOURI

1306 South Powell Road
Independence, MO 64057
800.747.0012 • 800.409.3069/Fax

JACKSONVILLE, FLORIDA

7110 Stuart Avenue
Jacksonville, FL 32254
800.394.4419 • 800.413.3292/Fax

JEFFERSON, OHIO

352 East Erie Street
Jefferson, OH 44047
800.321.5833 • 800.233.5719/Fax

MOCKSVILLE, NORTH CAROLINA

188 Quality Drive
Mocksville, NC 27028
800.228.6119 • 800.228.7916/Fax

NASHVILLE, TENNESSEE

4314 Hurricane Creek Boulevard
Antioch, TN 37013
800.251.8508 • 800.419.4372/Fax

NEW ALBANY, INDIANA

999 Park Place
New Albany, IN 47150
812.944.2733 • 812.944.1418/Fax

ROCK ISLAND, ILLINOIS

8111 29th Street West
Rock Island, IL 61201
800.747.1206 • 309.787.1833/Fax

ROGERS, MINNESOTA

22651 Industrial Boulevard
Rogers, MN 55374
800.328.9316 • 800.938.9119/Fax

SEATTLE, WASHINGTON

20213 84th Avenue South
Kent, WA 98032
800.431.3470 • 253.872.2008/Fax

SELLERSBURG, INDIANA

7800 State Road 60
Sellersburg, IN 47172
800.999.7777 • 800.477.9318/Fax

SIOUX FALLS, SOUTH DAKOTA

2700 West 3rd Street
Sioux Falls, SD 57104
888.299.0024 • 888.960.0429/Fax

SPOKANE, WASHINGTON

2727 East Trent Avenue
Spokane, WA 99202
800.572.6565 • 509.534.4427/Fax

TEMPLE, TEXAS

3838 North General Bruce Drive
Temple, TX 76501-6505
800.543.4415 • 800.543.4473/Fax

WOODLAND, CALIFORNIA

1326 Paddock Place
Woodland, CA 95776
800.759.6019 • 530.668.0901/Fax